SUPER HIGH PRESSURE KYOWA TESTER



Lightweight, Portable

For hydrostatic test of high pressure vessels, pipelines and equipment

FEATURES

- Achievement of high pressures 50, 300, 500, 1000kg/cm² by simple mechanism and simple operation
- Easy-to-carry handy type
- Lightweight and rust-free plastic tank, with dust-proof
- With direct-coupled type ball tap available for city water supply, ... easy to feed water
- Pressure gauge with 100ϕ large vibration absorber
- The closing valve is of special construction of Kyowa original design.
- T-50N is designed for large suction/discharge rate and lightweight, having the capacity several times the conventional model.
- T-50N is simply connected with a 1.5m high pressure hose with one-touch coupler.

SPECIFICATIONS

	Max pressure kg/cm ²	Plunger dia.	Stroke mm	Suction rate/stroke c.c.	Tank volume ℓ	Discharge nozzle size	Weight kg	Size L×H×W	Accessories
T-50NDX	50	30	45 .	32.0	18	3/8	8.0	610×375×290	Hose ass'y with coupler 3/8 × 1.5 m
T-300NDX	300	12	45	5.0	18	3/8	8.0	610×375×290	Hose ass'y 3/8 × 1m
T-500NDX	500	8	30	1.5	18	3/8	9.5	630×410×270	Hose ass'y 3/8 × 1m
T-1000NDX	1000	8	30	1.5	18	3/8	9.5	630×410×270	Hose ass'y 3/8 × 1m