HHM



Manufacturer of Test Pumps & High-Pressure Washing Machines — Offers

## **HYDRAULIC PRESSURE TEST PUMP**





KYOWA & TESTER

Utility model & design

[HAND OPERATED] Model T-50K-P/T-100K

## SPECIFICATIONS (50 kg/cm² pressure gauge is available if desired.)

Item Model	Maximum Pressure	Plunger Diameter	Stroke	Rate of Water Suction Per Stroke	Capacity of Water Tank	Size of Discharge Port	Weight	Dimensions L×H×W	Accessories
T-50K-P	50kg/cm²	22 <sup>m</sup> / <sub>m</sub>	35 <sup>m</sup> / <sub>m</sub>	13 c.c.	4.5ℓ Plastic tank	1/4	3.3kg	320×300 ×200 m/m	Pressure gauge ¼PT 1 Pressure hose 1 Union joint ½ 1 Bushing ½×¼ 1
T-100K	100 kg/cm²	22 <sup>m</sup> / <sub>m</sub>	35 ‰	13 c.c.	5.2 <i>l</i> Steel tank	1/4	7.0kg	370×300 ×210 m/m	Pressure gauge ¼ PT 1 Ultra high pressure hose ¼ PF×1m 1 ¼ nipple 1

\*SPecifications may be subject to change without notice. \*KYOWA's products are patented. Give careful attention to imitations

## ■FEATURES OF KYOWA TESTER

- 1. High-precision stainless steel (SUS 304) ball value is applied as the valve.
- 2. Valve seat is replaceable with ease.
- 3. Water tank of rust-free plastic (P.P.) construction assures unchanging cleanliness. (Models T-50K and T-100K are of vinyl-coated steel sheet construction.)
- 4. The plunger packing used is standard product, O-ring No. P-22 which is available in local hardware dealers.
- 5. All fulcrum pins applied are made of stainless steel.
- 6. A full range of accessories are provided to permit on-the-spot job
- 7. Matchless compact and light-weight design in the world.